

Date : 2022/08/12

Jiang Xi Cheng jiang new energy
Co.,Ltd
Wuning County Industrial Park,
Jiujiang City, Jiangxi
P.R. China
Attn:

Re. : US US Certificate

Type of Equipment : Li-ion Cell
Model Designation : See Certificate
Certificate No. : US 72227409 0001
File No. : CN22KAIM 001
Engineer/Contact : Sven Olaf Steinke
Standard(s) : UL 1642:2020

Dear Madame or Sir,

The above referenced technical equipment has been tested and was found to be in compliance with the listed test requirement(s). Enclosed, please find the TUV Rheinland approval document No. US 72227409 0001. It authorizes you to label the listed product(s) with the TUV Rheinland Mark identified in the approval document. For compliance, the Test Mark must be on the approved unit.

Your product is subject to regular factory follow-up inspections as well as annual certificate and factory registration fees.

In using the TUV Rheinland Mark you are obligated to comply with the TUV Rheinland of North America Service Agreement.

If we can be of any further assistance to you, please do not hesitate to contact us.

Sincerely yours,
Certification Body

Jason Tang
QA Certification Officer



Enclosure

Certificate



Certificate no.

US 72227409 01

License Holder:

Jiang Xi Cheng jiang new energy Co.,Ltd
Zhongcheng Industrial Park,
Wuning County Industrial Park,
Jiujiang City,
Jiangxi
P.R. China

Manufacturing Plant:

Jiang Xi Cheng jiang new energy Co.,Ltd
Zhongcheng Industrial Park,
Wuning County Industrial Park,
Jiujiang City,
Jiangxi
P.R. China

Test report no.: USA-SOS CN22KAIM 001

Client Reference:

Tested to: UL 1642:2020

Certified Product: Li-ion Cell

License Fee - Units

Model Designation: INR 18650-800mAh, INR 18650-900mAh
INR 18650-1000mAh, INR 18650-1200mAh, INR 18650-1300mAh
INR 18650-1500mAh, INR 18650-1800mAh, INR 18650-2000mAh
INR 18650-2200mAh, INR 18650-2500mAh, INR 18650-2600mAh
INR 18650-2800mAh, INR 18650-2900mAh, INR 18650-3000mAh
INR 18650-3200mAh

7

Rated Capacity: See Appendix (Constr. Data Form)
Rated Voltage: DC 3.7V
Discharging temperature: -20~45°C
Charging temperature: 0~50°C
Other Data: See Appendix (Constr. Data Form)

7

Appendix: 1

Licensed Test mark:



Date of Issue

(day/mo/yr)

12/08/2022